



Base Material	基材	ZINCALUME®, Clean COLORBOND®
Base metal thickness	ベース金属の厚さ	0.45mm ; 0.55mm*; 0.75mm*;
Cover width	動き幅	650 mm
Rib Height	リブの高さ	110 mm
Length	長さ	Lengths depend on customer's requirement 長さは顧客の要求に依存する
Tolerance	管理範囲	Length 長さ: +0mm, -15mm Cover width/ 動き幅: +4mm, -4mm
Coating mass	被覆質量	150g/m ²
Yield strength	降伏強度	300 MPa
ZINCALUME® steel meets Australian standard	オーストラリア基準を満たした ZINCALUME® 鋼	AS1397-G300 - AZ150
Clean COLORBOND® steel meets Australian standard	オーストラリア基準を満たした CLEAN COLORBOND® 鋼	AS/NZS 2728

(* Non-standard thickness
*注意：非標準的な厚さ



LYSAGHT® ULTRA RIB™ CONNECTOR - LYSAGHT® ULTRA-RIB™コネクター

PT. NS BlueScope Lysaght Indonesia

- **Sales & marketing office :**
Wisma BRI II lantai 9, Jl. Jendral Sudirman No 44-46, Jakarta 10210
T (021) 5790 5415 • F (021) 5790 5416
- **Jakarta** Jl. Irian Blok DD2/2 Kawasan Industri MM - 2100, Cibitung - Bekasi
T (021) 8998 2965 • F (021) 8998 2966
- **Surabaya** Jl. Raya Trosobo KM 24, Taman - Sidoarjo, T (031) 897 1279 • F (031) 897 1278
- **Medan** Jl. Rumah Potong Hewan No. 117, Medan, T (061) 685 1555 • F (061) 685 0155
- **Pekanbaru** Kompleks Pergudangan Pekanbaru Logistics Center Blok B7 - B8
Jl. Siak II Kelurahan Rumbai Bukit, Kecamatan Rumbai - Pekanbaru
T (0761) 7877 065
- **Palembang** Komplek Pergudangan Primastar Biz park blok K1, Jl. Tanjung Siapi api km 8.5 Palembang, T (0711) 911 5647 / 591 1199
- **Semarang** Kawasan Industri Candi, Blok 11A No.2, Jl. Gatot Subroto - Semarang
T (024) 7627 233 / 7627 235 • F (024) 7627 234
- **Makassar** Jl. Raya 1 No.1 Kawasan Industri Makassar (KIMA), Makassar
T (0411) 833 350 / 505 7999 • F (0411) 514 343



For further information, brochures, and your local distributor, please contact us :

• **T +62 21 578 54150**
• **F +62 21 5785 4151**
www.bluescopesteel.co.id

Hotline : **+62 811 8111 080**

Email : **Lysaghtmarketing@bluescopesteel.com**



What advantages you can get from LYSAGHT® ULTRA RIB™

Excellent waterproof

LYSAGHT® ULTRA RIB™ with special high rib and concealed fixing and seaming ensure the totally waterproof for the most strict requirement buildings.

Insulated option flexibility

Two types of high & low connectors helps the LYSAGHT® ULTRA RIB™ can go with normal or very thick and high-density insulation which fit with specific requirement.

Color in seaming roof

The LYSAGHT® ULTRA RIB™ can be supplied with Clean COLORBOND® material thanks to the special seaming principal.

High quality material

LYSAGHT® ULTRA RIB™ are made from aluminium/zinc alloy coated ZINCALUME® steel/ pre-painted Clean COLORBOND® steel that have a life time of up to four times that of ordinary Galvanised steel and excellent resistance to tropical discoloration and staining, bring a long lasting beauty and smart appearance to your project.

Cost Saving

The high rib, spanning ability, lightness and rigidity of LYSAGHT® ULTRA RIB™ profile permits wide support spacing which helps save cost of purlins in the building.

Smart Apperance

The stiff eners in profile circle node in the rib and electric seamers ensure the straight and good-looking roof at completion.

Low Roof Pitch

Can be used on roofs with a little as 2 degree.

Site Mobile Roll-Former

For project that required long length roof without any end laps, LYSAGHT® ULTRA RIB™ can be roll-formed at site by mobile roll-former with the length of the sheets up to 65 m.

LYSAGHT® ULTRA RIB™ の特徴

優秀な防水性

特別に高いリブ、ボルトレスシーム横造のため LYSAGHT® ULTRA-RIB™ は高い防水性を持ちます。

断熱なオプションの多様性

通常の断熱材、厚い断熱材、高密度の断熱材に対応できるよう、高さの異なる二種類のコネクターを準備しています。

色が選べます

LYSAGHT® ULTRA-RIB™ は、特別な継ぎ合わせ横造のおかげで Clean COLORBOND® の材料で供給できます。

高品質の材料

LYSAGHT® ULTRA-RIB™ は、ZINCALUME® 鋼又は事前塗装の Clean COLORBOND® を用いて生産されますので通常の亜鉛めっき鋼に対して4倍耐性があり、熱帯特有の変色や汚れに対して強く、長期間にわたって美しさを保ちます。

費用節約

LYSAGHT® ULTRA-RIB™ は高リブを持ち、軽量で剛性が高いためより広いスパンで施工でき、母屋のコストを下げることができます。

スマートな外見

中央部の凸起と電気シーマーによるかしめの効果で、直線的な美しい屋根に仕上がります。

低包配が可能

最低の屋根包配は2度です。

現場モバイルロールフォーマ

無エンドラップで長尺の屋根が必要な場合には、LYSAGHT® ULTRA-RIB™ はモバイルロールフォーマで65 mの長さまでロール形成できます。